

Signature _____

Name _____

cs30x _____

Student ID _____

Score: _____

Quiz 2
CSE 30
Winter 2009

#1. a) Write the SPARC assembly instructions to define the following **global** variables in the **data/bss** segment:

```
char Death_Cab[] = "April 29";  
short stack;
```

#2. What is the value (**in hex**) of %o1 after each set of instructions:

a)

```
set 0xDEADBEEF, %o1  
sra %o1, 16, %o1
```

Value in %o1 at this point is **0x**_____

b)

```
set 0xDEADBEEF, %o1  
set 0x4D3C2B1A, %o2  
xor %o1, %o2, %o1
```

Value in %o1 at this point is **0x**_____

c)

```
set 0xDEADBEEF, %o1  
set 0x4D3C2B1A, %o2  
and %o1, %o2, %o1
```

Value in %o1 at this point is **0x**_____

#3. Assume you run gdb on pal.

State how to set a breakpoint at the entry point in displayX():

Assume you correctly set this breakpoint and performed a run with correct command line arguments.

State how to print the value of the 2nd argument passed to displayX() in gdb:

(over)

#4. Write the equivalent **unoptimized** SPARC assembly language instructions to perform the following C code fragment. Use the loop construct specified in class/Notes.

C

```
for ( a = 9803; a > 181; --a )
{
    x = a - 345;
}
```

SPARC assembly

```
/* x is mapped to %12 */
/* a is mapped to %14 */
```

#5a. Write the equivalent **unoptimized** SPARC assembly language instructions to perform the following C code fragment.

C

```
x = x % 7007;
```

SPARC assembly

```
/* x is mapped to %10 */
```

5b. Now optimize your answer from #5a to eliminate any delay slots:

Optimized version of above SPARC assembly